ONKYO

TX-RZ730 9.2-Channel Network A/V Receiver



Full-scale sound and vision to revitalize your life

Here's a budget-friendly A/V receiver with the core power needed for 7.2.4-ch* Dolby Atmos® or DTS:X® playback at THX® Certified Select™ theater-reference volume to enhance the jaw-dropping spectacle of 4K HDR video as it unfolds on screen. Dynamic Audio Amplification blends high current with patented noise-reduction technology to achieve fluent transients, superb detail resolution, and wide 5 Hz-100 kHz frequency response. Music from any source is emotionally involving, from Hi-Res Audio to LP records to multi-room network music via Chromecast built-in, FlareConnect™, and DTS Play-Fi® technology. With 11.2-multichannel pre-outs, powered ZONE 2 and powered ZONE 3 speaker outputs, it's easy to configure a reliable home-theater layout and audio distribution setup that suits you. The TX-RZ730 streamlines entertainment with future-ready HDMI® handling Dolby Vision[™], HLG, and HDR10 formats. Premium AccuEQ Advance room-acoustic calibration with multi-point measurement ensures balanced sound. Just relax and soak up the magic only an Onkyo can deliver. * Requires outboard stereo power amplifier

HIGHLIGHTS

- 225 W per channel
- THX[®] Certified Select[™] theater-reference sound quality Dynamic Audio Amplification with 5 Hz–100 kHz
- reproduction + 5.2.4-ch Dolby Atmos® and DTS:X® (7.2.4-ch with external amp)
- HDMI® 7 In (I Front¹), Main Out, and Sub/Zone 2 Out⁺² supporting 4K/60 Hz, HDR10, HLG, Dolby Vision™, BT.2020, and HDCP 2.2 pass-through Chromecast built-in
- Works with the Google Assistant
- 5 GHz/2.4 GHz Wi-Fi[®], DTS Play-Fi[®] technology, FlareConnect[™], AirPlay, Amazon Music, Spotify, TIDAL, Deezer, Pandora®, Tuneln*3

ADVANCED FEATURES

- THX Certified Select theater-reference volume and sound quality • HDMI supports HDR10, HLG, Dolby Vision, BT.2020, and 4K/60 Hz pass-through and HDCP 2.2
- Dolby Atmos and DTS:X playback through 5.2.4 or 7.2.2 channels
- 11.2 multichannel pre-outs and processing for 7.2.4-ch playback with an external stereo power amp
- Powered ZONE 2 and powered ZONE 3 speaker outputs, Zone 2 and Zone 3 line-level outputs with DACs supporting digital** and analog audio playback
- Cross-compatible upmixing for Dolby® and DTS® soundtracks with Dolby Surround and DTS Neural:X $^{\rm w}$ solutions
- AccuEQ Advance room-acoustic calibration with standing
- wave correction
- AccuReflex $^{\scriptscriptstyle\rm M}$ phase alignment for Dolby Atmos-enabled speakers • Stable 5 GHz/2.4 GHz Wi-Fi connectivity
- Easy multi-room management with Onkyo Controller app*5
- Audio streaming with Chromecast built-in and voice control through devices with the Google Assistant built-in

- DTS Play-Fi multi-room audio distribution technology via Onkyo Music Control App*5
- · FlareConnect multi-room audio distribution to
- compatible components
- Supports audio streaming from iPad, iPhone, Mac, and iTunes via AirPlay • Amazon Music, Spotify, TIDAL, Pandora, and Deezer music
- streaming services and Tuneln internet radio Hi-Res Audio playback including DSD 5.6 MHz/2.8 MHz^{*6}
- 192 kHz/24-bit FLAC*7, WAV (RIFF)*7, AIFF, ALAC*7, and Dolby[®] TrueHD^{*8}
- Bluetooth® wireless audio technology for mobile, laptop, and PC (Version 4.1 + LE, Profile: A2DP v1.2, AVRCP v1.3)
- Advanced Music Optimizer improves compressed digital audio guality (Bluetooth audio included) • Built-in low-noise phono pre-amp for Moving Magnet (MM)
- cartridges • Supports Front L/R bi-amping
- 480i de-interlacing (480i to 480p) via HDMI for legacy video formats

AMPLIFICATION FEATURES

- 225 W/Ch (6 ohms, I kHz, 10% THD, I cha nnel driven): 100 W/Ch (8 ohms, 20 Hz-20 kHz, 0.08% THD, 2 channels driven, FTC)
- Dynamic Audio Amplification with 5 Hz–100 kHz reproduction
- High-current power to drive large speakers with 4-ohm resistance
- H.C.P.S. (High Current Power Supply) customized transformer
- Extra-large customized block capacitors for instant power • VLSC (Vector Linear Shaping Circuitry) high-frequency noise removal
- technology (Front L/R channels) Non-phase-shift amp circuitry for a clear and cohesive audio image
- · Discrete output stage circuitry for low distortion

PROCESSING FEATURES

- \bullet Dolby Atmos and DTS:X reproduction through 5.2.4-ch or 7.2.2-ch (7.2.4-ch with external stereo power amp)
- HDMI support for 4K/60 Hz, HDRI0, HLG, Dolby Vision, 3D, Audio Return Channel, DeepColor[™], xv.Color[™], LipSync, Dolby Atmos, Dolby TrueHD, DTS:X, DTS-HD[®] Master Audio[™], DSD, DVD-Audio, Super Audio CD (SACD), multichannel PCM, and CEC • Precision AKM (AK4458) 384 kHz/32-bit multichannel DAC

- PLL (Phase Locked Loop) jitter-cleaning technology for S/PDIF audio
- 32-bit Digital Signal Processing (DSP)
- · Listening modes for gaming (Rock, Sports, Action, and RPG)
- Theater-Dimensional virtual surround-sound function · Direct Mode for audio reproduction close to original source quality
- Independent tone controls (bass/treble) for all channels

CONNECTION FEATURES

- 7 HDMI inputs (I Front), Main Out, and Sub/Zone 2 Out
- Powered USB terminal (5 V, 1 A) for audio playback (rear)
- 2 composite video inputs and 2 component video inputs
- 3 digital audio inputs (2 optical and 1 coaxial)
- 6 analog audio inputs, I stereo 1/8" (3.5 mm) analog input (front)
- Phono input (MM) and equalizer for turntable connection
- 11.2 multichannel pre-outs
- 2 subwoofer pre-outs
- 1/4" (6.35 mm) headphone jack (front)
- Speaker setup mic input (front) • Banana-plug-compatible speaker posts
- 12 V trigger output, IR input, IP control, and RS232 support
- · Detachable power cable

OTHER FEATURES

- Crossover adjustment for each channel
- (40/50/60/70/80/90/100/120/150/180/200 Hz)
- A/V Sync Control (up to 500 ms in 5 ms steps at 48 kHz)
- · Graphical User Interface with overlaid On-Screen Display via HDMI
- Ouick Setup Guide via GUI
- Economical HDMI pass-through and Network Standby functions
- 3-mode display dimmer (Normal/Dim/Dimmer)
- 40 FM/AM random presets

Simple remote control

• Rack-mounting kit (optional IRK-155-3D) Nack-mounting ktt (optional IKK-155-3D)
First HDMI input does not support 4KI/60Hz/RGB/4:4:4/4:2:.2. *2 Sub/Zone 2 HDMI does not support ARC or CEC. *3 Availability of services may vary with region. Subscription may also be required. *4 Audio via HDMI inputs and S/PDIF audio not supported in Zone 3.*5 Wist App Store or the Coogle Phy Store to check device and OS requirements and download free. *6 Converted to PCM. Playback not guaranteed via wireless LAN. *7 Playback not guaranteed via wireless LAN. Supported sampling rate via wireless LAN depends on network environment. *8 Playback not guaranteed via wireless LAN.

TX-RZ730 9.2-Channel Network A/V Receiver

THX[®] Certified Select[™] theater-reference audio

THX Certified Select guarantees theater-reference sound in your home. To gain certification, amplifiers must pass severe bench-tests covering every aspect of performance. THX Certified Select components suit rooms where screen-toseat distance is about 10 ft. (3 m) and volume 2,000 cubic feet (57 m³).



Introducing the RZ Series: more than better sound

Our RZ Series takes performance and build-quality to the next level for a reference experience. Custom high-current transformer, customized block capacitors, and other upgraded

parts deliver 5 Hz-100 kHz frequency response for wall-shaking bass, clean treble. and fast dynamics. RZ Series supports a variety of home theater and multi-room layouts to suit you, while details such as 12 V trigger, RS-232C, IP Control, and IR input make home integration easy.



Customized high-current capacito

Dynamic Audio Amplification (DAA)

The DAA philosophy places less emphasis on lab measurements and more on how the sound actually feels in real life. High-current drive and expert tuning deliver natural transient response, the key to involving sound. A deep power reserve arrives instantly when action explodes on screen, adding adrenaline to the film experience. Accuracy and control is maintained with custom transformer and block capacitors, non-phase-shift amp circuitry, and discrete output transistors. With VLSC[™] noise filtering (Front L/R) for improved fidelity, DAA is built for compelling sound.

Dolby Atmos® and DTS:X® at up to 7.2.4 channels

Hear Dolby Atmos and DTS:X soundtracks through 7.2.2 or 5.2.4 channels. Connect an outboard power amp

via 11.2-multichannel pre-outs and enjoy seamless top-to-bottom, side-to-side, and front-back coverage with

four in-ceiling speakers and seven floor-standers. Individual sounds aren't tied to channels and move naturally around your audience.



Dolby® and DTS® solutions for 3D sound

DTS Neural:X $^{\scriptscriptstyle \rm M}$ technology and Dolby Surround find cues in legacy soundtracks and upmix for playback through systems with height channels. Cross-compatible with Dolby® and DTS® formats, enjoy spatially realistic and natural sound from your existing DVD and Blu-ray Disc™ library or via movie streaming service.

Chromecast built-in works with the Google Assistant

Stream any music from your smartphone, laptop, or PC to the receiver with ease. Control playback with Chromecast-enabled apps from your iPhone, iPad, Android[™] phone or tablet, Mac or Windows laptop, or Chromebook™. If you have a device with the Google Assistant, you can control music on the TX-RZ730 by voice.





Ready for DTS Play-Fi® multi-room audio technology

DTS Play-Fi technology allows you to enjoy quality music from online services, media server, and mobile device to any number

FlareConnect[™] wireless multi-room audio

input sources between compatible components. Enjoy

FlareConnect shares audio from network and external audio

effortless multi-room playback of LP records, CDs, network

music services, and more with supported components and

speaker systems. Music selection, speaker grouping, and

playback management across the home are built into the

Note: For external input availability visit http://www.onkyo.com/flareconnect. Download Onkyo Controller free from the App Store or the Google Play Store.

With a 5.2-ch theater layout in Zone I (Main), the remaining four channels can drive speakers in Zone 2 and Zone 3. As

well as analog distribution, dedicated DACs enable digital

sources* to be synced across rooms simultaneously, or a

unique source to be played in every zone at once. Zone 2

* Audio via HDMI inputs and S/PDIF audio not supported in Zone 3.

AccuEQ Advance for Accurate Calibration

In addition, AccuEQ Advance employs multi-point

measurement to remove standing waves from your

AccuEQ sets speaker distance, SP level, and crossover.

listening space, which compromise audio quality and bass

response. The technology also detects and compensates

for background noise, such as the hum from an HVAC, to

AccuEQ

ADVANCE

Built-in 5 GHz/2.4 GHz Wi-Fi provides network stability for

Bluetooth wireless technology is also on board for easy mobile

AirPlay, streaming services, and internet radio built in

Find and stream music from iPad, iPhone, Mac, and PC over

the Apple AirPlay wireless audio platform. Further, Amazon Music, Spotify, TIDAL, Deezer, Pandora®, and TuneIn are all baked into the system GUI, making selection easy using Onkyo

Controller or Onkyo Music Control App.

streaming, Onkyo Controller app, and multi-room audio.

Wi-Fi® and Bluetooth® wireless connectivity

and Zone 3 line-level outputs are ideal for sharing sources to

Powered sound in three zones

existing hi-fi systems.

ensure accurate equalization.

or laptop connection.

of compatible products using Onkyo Music Control App. DTS Play-Fi technology can synchronize music in every room.

Onkyo Controller app.



t-lare connect

Supports 4K HDR, BT.2020, 4K/60 Hz, and HDCP 2.2

Welcome film-like 4K video bursting with bright and vibrant colors enabled by High Dynamic Range (HDR) to your supported TV display or projector. The receiver's HDMI® inputs, Main Out, and Sub/Zone 2 Out pass HDR10, HLG, and Dolby Vision[™] formats through to compatible displays. These terminals support the BT.2020 4K video standard, 4K/60 Hz playback, and HDCP 2.2.



SPECIFICATIONS

SPECIFICATION	13
Amplifier Section	
Power output	
All channels	225 W/Ch (6 ohms, 1 kHz, 10% THD,
	I channel driven)
	100 W/Ch (8 ohms, 20 Hz–20 kHz,
	0.08% THD, 2 channels driven, FTC)
Dumennie neuven	250 W (3 ohms, Front)
Dynamic power	220 W (4 ohms, Front)
	130 W (8 ohms, Front)
THD+N (Total Harmonic	
	0.08% (20 Hz–20 kHz, half power)
Input sensitivity and impe	dance
1	200 mV/47 k-ohms (Line)
	3.5 mV/47 k-ohms (Phono)
Rated RCA output level a	
Rated RCA output level a	
	I V/470 ohms (Subwoofer pre-out)
	I V/2.3 k-ohms (Zone pre-out)
	I V/200 mV/470 ohms (Zone pre/line-out)
Frequency response	5 Hz–100 kHz/+1 dB, -3 dB (Direct Mode)
Tone control	±10 dB, 20 Hz (Bass)
	±10 dB, 20 kHz (Treble)
Signal to Naisa natio	106 dB (Line, IHF-A)
Signal-to-Noise ratio	
	80 dB (Phono, IHF-A)
Speaker impedance	4 ohms–16 ohms
Video Section	
	and an alternative second
Input sensitivity/output le	
Video	I.0 Vp–p/75 ohms (Component Y)
	0.7 Vp–p/75 ohms (Component B/R)
	1.0 Vp–p/75 ohms (Composite)
Tuner Section	
Tuning frequency range	
FM	075 MIL 1070 MIL
	87.5 MHz-107.9 MHz
AM	530 kHz–1,710 kHz
FM/AM preset memory	40 stations
General	
Power supply	AC 120 V~, 60 Hz
Power consumption	750 W
No-sound power consum	ntion
to-sound power consum	70 W
Standby power consumpt	
	0.15 W
Dimensions (W x H x D)	17 1/8" × 6 15/16" × 14 15/16"
, , ,	(435 x 177 x 379.5 mm)
Weight	23.8 lbs. (10.8 kg)
v v eigitt	2.5.0 IDS. (10.0 Kg)
UPC CODE	
(B)	889951001317
CARTON	
	00.71 / 11.51 / 10.71 /
Dimensions (W x H x D)	22 ⁷ /16″ × 11 ⁵ /16″ × 18 ⁷ /16″
	(570 × 288 × 468 mm)
Weight	29.8 lbs. (13.5 kg)

Supplied Accessories

Power cord • Indoor FM antenna • AM loop antenna
Speaker setup microphone • Quick Start Guide • Basic Manual
Remote controller • AAA (R03) batteries x 2

2 • 0 0 0 00 0 0 0 00 0 0 0 0 000 0 0 00 ۲ (GAME)

Text on receiver may vary with region

Due to a policy of continuous product improvement, Onlyo reserves the right to change specifications and appearance without notice. THX and the THX logo are trademarks of THX Ltd, registered in the U.S. and other countries. THX CERTIFIED SELECT and the THX SELECT application icon are trademarks of THX Ltd. Dolby, Dolby Atmos, Dolby Surround, Dolby Vision, and the double-D symbol are trademarks of Dolby Laboratories. For DTS patents, see http://patents.dts.com. Manufactured under license from DTS Leensing Limited. DTS, the Symbol, DTS and the Symbol together, DTSX, the DTSX logo, DTS NeuralX, Play-F, and the Play-Fi logo are registered trademarks of Dolby. Laboratories. For DTS patents, see http://patents.dts.com. Manufactured under license from DTS Leensing Limited. DTS, the Symbol, DTS and the Symbol together, DTSX, the DTSX logo, DTS NeuralX, Play-F, and the Play-Fi logo are registered trademarks or MPM licensing Administrator, Inc. In the United States and other countries. The Bluetoxth SG, Coogle Play, Chense, Play, Play, and Max are trademarks of Apple Inc., Resistened in the U.S. and other router and Max are trademarks of Apple Inc., Resistened that the use of this accessory with iPhone or Play assistant requires an internet connection and in on tax-and have are trademarks of Apple Inc., Resistened in the U.S. and other router and other router marks and logos are trademarks of Coogle LLC. The Coogle Acstistant requires an internet connection and in an Imagages or countries. Controlling estimates and Play with SS subscriptions for services and applications may be required and additional terms, conditions and/or charges may apply. WichFF is a registered trademark of the Wr-Fi Aliance. The Wr-Fi CERTIFIED Logo is a certification mark of the Wr-Fi Aliance. Spottif foroup, registered in the U.S. and other countries. Products displaying the Hi-Res Audo logo conform to the Hi-Res Audo logo is used under license from Japa Audio Society. The Hi-Res Audo logo is used under license from Japa Audio Society. PANDORA I



Copyright © 2018 Onkyo Corporation. All rights reserved.