ONKYO

TX-RZ830 9.2-Channel Network A/V Receiver



Entertainment like you've never felt it before

Feed your speakers the sound they deserve with the TX-RZ830, Onkyo's premier mid-class A/V receiver, and unlock complete 7.2.4-ch object-based audio coverage (outboard stereo amp required), universal 4K HDR pass-through, and custom Dynamic Audio Amplification housed in a robust aluminum-fronted chassis. Sound is fluid, expressive, and dynamically faithful to the source, details resolving with astonishing transparency, ideal for high-resolution music including Direct DSD 11.2 MHz, LPs via phono pre-amp, SACD from Blu-ray[™] player, or music streamed over AirPlay. Compatibility with popular wireless audio platforms allows the TX-RZ830 to fit in seamlessly with other compatible components for easy multi-room audio. Mobile apps synchronize the content you want in different spaces with Chromecast built-in, DTS Play-Fi® technology, or FlareConnect[™]. TIDAL, Amazon Music, Spotify, Deezer, and Tuneln are built in for easy navigation. Do your favorites a favor: order the TX-RZ830 and bring what you love to life.

HIGHLIGHTS

- 250 W per channel
- THX[®] Certified Select[™] theater-reference sound quality
- Dynamic Audio Amplification with 5 Hz-100 kHz
- reproduction • 5.2.4-ch Dolby Atmos® and DTS:X®
- (7.2.4-ch with external amp) HDMI® 7 In (1 Front"), Main Out, and Sub/Zone 2 Out"² supporting 4K/60 Hz, HDR10, HLG, Dolby Vision[™], BT.2020, and HDCP 2.2 pass-through
- Chromecast built-in
- Works with the Google Assistant
- 5 GHz/2.4 GHz Wi-Fi[®], DTS Play-Fi[®] technology, FlareConnect[™], AirPlay, Amazon Music, Spotify, TIDAL, Deezer, Pandora®, Tuneln*3

ADVANCED FEATURES

- THX Certified Select theater-reference volume and sound quality
- HDMI supports HDR10, HLG, Dolby Vision, BT.2020, and 4K/60 Hz pass-through and HDCP 2.2
- Dolby Atmos and DTS:X playback through 5.2.4 or 7.2.2 channels • 11.2 multichannel pre-outs and processing for 7.2.4-ch playback with
- an external stereo power amp Powered ZONE 2 and powered ZONE 3 speaker outputs, Zone 2 and Zone 3 pre-/line-level outputs with DACs for digital⁸⁴ and analog
- audio playback
- Cross-compatible upmixing for Dolby® and DTS® soundtracks with Dolby Surround and DTS Neural:X $^{\rm w}$ solutions
- AccuEQ Advance room-acoustic calibration with standing wave correction and AccuReflex[™] phase-alignment for Dolby Atmos-enabled speakers
- Stable 5 GHz/2.4 GHz Wi-Fi connectivity Easy multi-room management with Onkyo Controller app*s
- Audio streaming with Chromecast built-in and voice control through devices with the Google Assistant built-in
- DTS Play-Fi multi-room audio distribution technology via Onkyo Music Control App^{*5}

- FlareConnect multi-room audio distribution to
- compatible components Supports audio streaming from iPad, iPhone, Mac, and iTunes via AirPlay

- Hi-Res Audio playback including DSD 11.2/5.6/2.8 MHz*6, 192 kHz/ 24-bit FLAC*7, WAV (RIFF)*7, AIFF, ALAC*7, and Dolby® TrueHD*
- Bluetooth® wireless audio technology for mobile, laptop, and PC (Version 4.1 + LE, Profile: A2DP v1.2, AVRCP v1.3)
- Advanced Music Optimizer improves compressed digital audio quality (Bluetooth audio included)
- ${\scriptstyle \bullet}$ Built-in low-noise phono pre-amp for Moving Magnet (MM) cartridges Supports Front L/R bi-amping
- 480i de-interlacing (480i to 480p) via HDMI for legacy video formats

AMPLIFICATION FEATURES

- 250 W/Ch (6 ohms, 1 kHz, 10% THD, 1 channel driven); 120 W/Ch (8 ohms, 20 Hz-20 kHz, 0.08% THD, 2 channels driven, FTC)
- Onkyo high-current digital Dynamic Audio Amplification system
- 5 Hz-100 kHz reproduction and high power to drive 4-ohm speakers • H.C.P.S. (High Current Power Supply) customized transformer
- Extra-large customized block capacitors for instant power
- VLSC (Vector Linear Shaping Circuitry) high-frequency noise removal technology (Front L/R channels)
- · Non-phase-shift amp circuitry for a clear and cohesive audio image Discrete output stage circuitry for low distortion

PROCESSING FEATURES

- Dolby Atmos and DTS:X reproduction through 5.2.4-ch or 7.2.2-ch (7.2.4-ch with external stereo power amp)
- HDMI support for 4K/60 Hz, HDR10, HLG, Dolby Vision, 3D, Audio Return Channel, DeepColor^{*}, xv.Color^{*}, LipSync, Dolby Atmos, Dolby TrueHD, DTS:X, DTS-HD[®] Master Audio^{**}, DSD, DVD-Audio, Super Audio CD (SACD), multichannel PCM, and CEC Precision AKM (AK4458) 384 kHz/32-bit multichannel DAC
- PLL (Phase Locked Loop) jitter-cleaning technology for S/PDIF audio
- 32-bit Digital Signal Processing (DSP)
- · Pristine reproduction of audio-only sources in Pure Audio Mode

- Listening modes for gaming (Rock, Sports, Action, and RPG)
- · Theater-Dimensional virtual surround-sound function
- · Direct Mode for audio reproduction close to original source quality Independent tone controls (bass/treble) for all channels

CONNECTION FEATURES

- 7 HDMI inputs (I Front), Main Out, and Sub/Zone 2 Out
- · Powered USB terminal (5 V, I A) for audio playback (rear)
- 2 composite video inputs and 2 component video inputs
- 3 digital audio inputs (2 optical and 1 coaxial)
- 6 analog audio inputs
- Phono input (MM) and equalizer for turntable connection
 II.2 multichannel pre-outs
- 2 subwoofer pre-outs
- 1/4" (6.35 mm) headphone jack (front)
- Speaker setup mic input (front)
- Banana-plug-compatible speaker posts • 12 V trigger output, IR input, IP control, and RS232 support
- · Detachable power cable

OTHER FEATURES

- · Aluminum front panel, flap door, and volume control
- Crossover adjustment for each channel (40/50/60/70/80/90/100/120/150/180/200 Hz)
- A/V Sync Control (up to 500 ms in 5 ms steps at 48 kHz)
- Graphical User Interface with overlaid On-Screen Display via HDMI
- Ouick Setup Guide via GUI
- Economical HDMI pass-through and Network Standby functions
- 3-mode display dimmer (Normal/Dim/Dimmer)
- 40 FM/AM random presets Simple remote control
- Rack-mounting kit (optional IRK-180-4C)

Kack-mounting kit (optional IKK-180-4()) I Front HDM limpt does not support 4K/06/Hz/RGB/4-4/14:2:2.*2 Sub/Zone 2 HDMI does not support ARC or CEC.*3 Availability of services may vary with region. Subscription may also be required. *4 Availa via HDMI inputs and S/PD/F availa not support and in Zone 3.*5 Visit App Store or the Google Play Store to check device and OS requirements and download free.*6 ISDS 11.2 MHz playback is native. DSD 50.28 MHz is converted to PC/M before playback. Rhayback not guaranteed via wireless LAN. *7 Rayback not guaranteed via wireless LAN depends on network environment.*8 Playback not guaranteed via wireless LAN. *8 Playback not guaranteed via wireless LAN.

Introducing the TX-RZ830

The TX-RZ830 brings a high-end approach to build and sound to the middle of our A/V receiver range. Our top-of-the-line high-current digital architecture is deployed with spectacular results: fluency, frequency range, transient response, and detail resolution are unassailable at the price. With sheer high-current power needed for edge-of-the-seat movie thrills and joyful stereo listening, the TX-RZ830 presents as a high-fidelity reference component loaded with connections needed for a custom install lasting well into the future.

THX[®] Certified Select[™] theater-reference audio

THX Certified Select guarantees theater-reference sound in your home. To gain certification, amplifiers must pass severe bench-tests covering every aspect of performance. THX Certified Select components suit rooms where screen-to-seat distance is about 10 ft. (3 m) and volume 2,000 cubic feet (57 m³).



Dynamic Audio Amplification (DAA)

The DAA philosophy places less emphasis on lab measurements and more on how the sound actually feels in real life. High-current drive and expert tuning deliver natural transient response, the key to involving sound. A deep power reserve arrives instantly when action explodes on screen, adding adrenaline to the film experience. Accuracy

and control is maintained with custom transformer and custom block capacitors, aluminum heat sink, non-phase-shift amp circuitry, and discrete output transistors. With VLSC $^{\odot}$ noise filtering (Front L/R) for improved fidelity, DAA is built for compelling sound.



Dolby Atmos® and DTS:X® at up to 7.2.4 channels

Hear Dolby Atmos and DTS:X soundtracks through 7.2.2 or 5.2.4 channels. Connect an outboard power amp via 11.2-multichannel pre-outs for even more expansive 7.2.4-ch plavback. Eniov seamless top-to-bottom, side-to-side.

and front-back coverage with in-ceiling speakers and floorstanding speakers. Individual sounds aren't tied to channels and move around your audience.




Dolby® and DTS® solutions for 3D sound

DTS Neural:X[™] technology and Dolby Surround find cues in legacy soundtracks and upmix for playback through systems with height channels. Cross-compatible with Dolby[®] and DTS[®] formats, enjoy spatially realistic and natural sound from your existing DVD and Blu-ray Disc[™] library or streaming service.

Chromecast built-in works with the Google Assistant

Stream any music from your smartphone, laptop, or PC to the receiver with ease. Control playback with Chromecast-enabled apps from your iPhone, iPad, Android[™] phone or tablet, Mac or Windows laptop, or Chromebook[™]. If you have a device with the Google Assistant built-in, you can control music on the TX-RZB30 by voice.





Ready for DTS Play-Fi® multi-room audio technology

DTS Play-Fi technology allows you to enjoy quality music from online services, media server, and mobile device to any number

FlareConnect[™] wireless multi-room audio

input sources between compatible components. Enjoy

FlareConnect shares audio from network and external audio

effortless multi-room playback of LP records, CDs, network

music services, and more with supported components and

speaker systems. Music selection, speaker grouping, and

playback management across the home are built into the

Note: For external input availability visit <u>http://www.onkyo.com/flareconnect</u>. Download Onkyo Controller free from the App Store or the Google Play Store

With a 5.2-ch theater layout in Zone 1 (Main), the remaining four channels can drive speakers in Zone 2 and Zone 3. As

well as analog distribution, dedicated DACs enable digital

sources* to be synced across rooms simultaneously, or a unique source to be played in every zone at once. Zone 2

* Audio via HDMI inputs and S/PDIF audio not supported in Zone 3

AccuEQ Advance for Accurate Calibration

In addition, AccuEQ Advance employs multi-point measurement to remove standing waves from your

AccuEQ sets speaker distance, SP level, and crossover.

listening space, which compromise audio quality and bass

response. The technology also detects and compensates for background noise, such as the hum from an HVAC, to

AccuEQ

A D V A N C E

Built-in 5 GHz/2.4 GHz Wi-Fi provides network stability for

Bluetooth wireless technology is also on board for easy mobile

AirPlay, streaming services, and internet radio built in

Find and stream music from iPad, iPhone, Mac, and PC over

the Apple AirPlay wireless audio platform. Further, Amazon

Music, Spotify, TIDAL, Deezer, Pandora®, and TuneIn are all

Controller or Onkyo Music Control App.

baked into the system GUI, making selection easy using Onkyo

streaming, Onkyo Controller app, and multi-room audio.

Wi-Fi[®] and Bluetooth[®] wireless connectivity

and Zone 3 pre-/line outputs are ideal for sharing sources to

Powered sound in three zones

existing hi-fi systems.

ensure accurate equalization.

or laptop connection.

of compatible products using Onkyo Music Control App. DTS Play-Fi technology can synchronize music in every room.

Onkyo Controller app.



(0 to la re

Supports 4K HDR, BT.2020, 4K/60 Hz, and HDCP 2.2

Welcome film-like 4K video bursting with bright and vibrant colors enabled by High Dynamic Range (HDR) to your supported TV display or projector. The receiver's HDMI® inputs, Main Out, and Sub/Zone 2 Out pass HDR10, HLG, and Dolby Vision[™] formats through to compatible displays. These terminals support the BT.2020 4K video standard, 4K/60 Hz playback, and HDCP 2.2.



SPECIFICATIONS

SPECIFICATIONS	
Amplifier Section	
Power output	
All channels	250 W/Ch (6 ohms, 1 kHz, 10% THD,
	I channel driven)
	120 W/Ch (8 ohms, 20 Hz-20 kHz,
	0.08% THD, 2 channels driven, FTC)
Dynamic power	250 W (3 ohms, Front)
	220 W (4 ohms, Front)
	130 W (8 ohms, Front)
THD+N (Total Harmonic	
TTID TN (TOLAI TIAI MONIC	0.08% (20 Hz–20 kHz, half power)
Input sensitivity and impe	
	200 mV/47 k-ohms (Line)
	3.5 mV/47 k-ohms (Phono)
Rated RCA output level a	
	I V/470 ohms (Subwoofer pre-out)
	I V/2.3 k-ohms (Zone pre-out)
	I V/200 mV/470 ohms (Zone pre/line-out)
Frequency response	5 Hz–100 kHz/+1 dB, -3 dB (Direct Mode)
Tone control	±10 dB, 20 Hz (Bass)
	±10 dB, 20 kHz (Treble)
Signal-to-Noise ratio	106 dB (Line, IHF-A)
	80 dB (Phono, IHF-A)
Spoakor impodanco	4 ohms–16 ohms
Speaker impedance	
Video Section	
Input sensitivity/output le	vel and impedance
Video	I.0 Vp–p/75 ohms (Component Y)
	0.7 Vp–p/75 ohms (Component B/R)
	1.0 Vp-p/75 ohms (Composite)
Tuner Section	
Tuning frequency range	
FM	07.5 MIL 107.0 MIL
	87.5 MHz–107.9 MHz
AM	530 kHz–1,710 kHz
FM/AM preset memory	40 stations
General	
Power supply	AC 120 V~, 60 Hz
	870 W
Power consumption	
No-sound power consum	
	70 W
Standby power consumpt	
	0.15 W
Dimensions (W x H x D)	17 1/8" x 7 15/16" x 15 11/16"
,	(435 × 201.5 × 398 mm)
Weight	30.9 lbs. (14.0 kg)
	50.7 103. (1 1.0 Kg)
UPC CODE	
(B)	889951001287
À	
CARTON	
Dimensions (W x H x D)	22 ⁵ /8" × 13 ³ / ₁₆ " × 19 ⁵ / ₁₆ "
	(574 × 335 × 490 mm)
Weight	37.5 lbs. (17.0 kg)

Supplied Accessories

 Power cord • Indoor FM antenna • AM loop antenna Speaker setup microphone • Quick Start Guide • Basic Manual Remote controller • AAA (R03) batteries x 2

Text on receiver may vary with region.

Due to a policy of continuous product improvement. Onlyo reserves the right to charge specifications and appearance without notice. THX and the THX log are trademarks of THX Ltd, registered in the U.S. and other countries. THX CERTIFED SELECT and the THX SELECT application icon are trademarks of THX Ltd. Dolby, Dolby Atmos, Dolby Surround, Dolby Vision, and the double-D symbol are trademarks of Dolby Laboratories. For DTS patents, see http://patentsdts.com. Manufactured under license from DTS Licensing Limited DTS, the Symbol, DTS and the Symbol together. DTSX, the DTSX dogo, DTS NeuralX, Play-F, and the Play-F. The Source's and other countries. The Bluetodth SC, and the Play-F, and the United States and other countries. The Bluetodth SC, and the Play-F, and the United States and other countries. The Bluetodth SC, dooge Play. Crowneasts built and other relater marks of Opple trans-sec entradewarks of the Play-F, and the sec of this accessory with iPhone on Play and the Southy Coope Play. The concests built and other relater marks and loggs are trademarks of the V-F, Te Conge LC. The Coope Sec Assistant requires an internet connection and is not analysae or countries. Controlling estimates and they southy concests built and additional terms, contisons and/or charges may apply. Wi-FP[®] is a registered trademark of the W-F, ERTIFED Logo is a certification mark of the W-

NPR No. 18N11 04/18

ONKYO. http://www.onkyousa.com/

Copyright $\ensuremath{\textcircled{O}}$ 2018 Onkyo Corporation. All rights reserved.